

Date: 24/05/2023 Page 1/10 Revision: N°1 (01/03/2022)

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: AEROSOL TEINTE RAL 400ML

Product code: A400-TEINTE-UFI. UFI: UY23-50SA-D00C-Q7S6

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Registered company name: SOLTA GROUPE.

Address: ZAC DES GRAVELLES 2 RUE DES CHENES ROUGES.91580.ETRECHY.FRANCE.

Telephone: 01.60.80.47.47. Fax: 01.60.80.48.48.

n.masseau@solta.fr www.solta.fr

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS02

GHS07

Signal Word : DANGER

Product identifiers:

607-025-00-1 N-BUTYL ACETATE

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ ...

Precautionary statements - Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Date: 24/05/2023 Page 2/10 Version: N°2 (16/06/2022) Revision: N°1 (01/03/2022)

AEROSOL TEINTE RAL 400ML - A400-TEINTE-UFI

P312 Call a POISON CENTER/doctor/... if you feel unwell.

Precautionary statements - Storage:

Store locked up.

P410 + P412Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements - Disposal:

P501 Dispose of contents/container to a licensed disposal facility

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

| Identification | (EC) 1272/2008 | Note | % |
|---------------------------------|--------------------|------|-----------------------|
| INDEX: 603-019-00-8 | GHS02, GHS04 | [1] | $50 \le x \% \le 100$ |
| CAS: 115-10-6 | Dgr | [7] | |
| EC: 204-065-8 | Flam. Gas 1, H220 | | |
| | | | |
| DIMETHYL ETHER | | | |
| INDEX: 607-025-00-1 | GHS02, GHS07 | [1] | $25 \le x \% < 50$ |
| CAS: 123-86-4 | Wng | | |
| EC: 204-658-1 | Flam. Liq. 3, H226 | | |
| REACH: 01-2119485493-29 | STOT SE 3, H336 | | |
| | EUH:066 | | |
| N-BUTYL ACETATE | | | |
| INDEX: 606-001-00-8 | GHS02, GHS07 | [1] | $10 \le x \% < 25$ |
| CAS: 67-64-1 | Dgr | | |
| EC: 200-662-2 | Flam. Liq. 2, H225 | | |
| | Eye Irrit. 2, H319 | | |
| ACETONE | STOT SE 3, H336 | | |
| | EUH:066 | | |
| INDEX: 607-195-00-7 | GHS02 | [1] | $2.5 \le x \% < 10$ |
| CAS: 108-65-6 | Wng | | |
| EC: 203-603-9 | Flam. Liq. 3, H226 | | |
| REACH: 01-2119475791-29 | | | |
| | | | |
| 2-METHOXY-1-METHYLETHYL ACETATE | | | |
| INDEX: SUB 19/32 | | [1] | $2.5 \le x \% < 10$ |
| CAS: 13463-67-7 | | | |
| EC: 236-675-5 | | | |
| REACH: 01-2119489379-17 0014 | | | |
| | | | |
| DIOXYDE DE TITANE | | | |

Information on ingredients:

(Full text of H-phrases: see section 16)

- [1] Substance for which maximum workplace exposure limits are available.
- [7] Propellant gas

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation:

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

Date: 24/05/2023 Page 3/10 Revision: N°1 (01/03/2022)

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of inhalation of spray mist, seek medical attention immediately, showing the packaging or label.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

Date: 24/05/2023 Page 4/10

Revision: N°1 (01/03/2022)

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

Date: 24/05/2023 Page 5/10

Revision: N°1 (01/03/2022)

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

| CAS | VME-mg/r | n3 : VME-ppm : | VLE-mg/m3: | VLE-ppm: | Notes: | |
|----------|----------|----------------|------------|----------|--------|--|
| 115-10-6 | 1920 | 1000 | - | - | - | |
| 123-86-4 | 241 | 50 | 723 | 150 | | |
| 67-64-1 | 1210 | 500 | - | - | - | |
| 108-65-6 | 275 | 50 | 550 | 100 | Peau | |

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

| CAS | TWA: | STEL: | Ceiling: | Definition: | Criteria: |
|------------|----------|---------|----------|-------------|-----------|
| 123-86-4 | 150 ppm | 200 ppm | | | |
| 67-64-1 | 500 ppm | 750 ppm | | A4; BEI | |
| 13463-67-7 | 10 mg/m3 | | | A4 | |

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

| CAS | VME: | VME: | Excess | Notes |
|----------|------|------------------------|--------|-------|
| 115-10-6 | | 1000 ppm | | 8(II) |
| | | 1900 mg/m ³ | | |
| 123-86-4 | | 62 ppm | | 2 (I) |
| | | 300 mg/m ³ | | |
| 67-64-1 | | 500 ppm | | 2(I) |
| | | 1200 mg/m ³ | | |
| 108-65-6 | | 50 ppm | | 1(I) |
| | | 270 mg/m ³ | | |

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

| CAS | VME-ppm: | VME-mg/m3: | VLE-ppm: | VLE-mg/m3: | Notes: | TMP No: |
|------------|----------|------------|----------|------------|--------|---------|
| 115-10-6 | 1000 | 1920 | - | - | - | - |
| 123-86-4 | 50 | 241 | 150 | 723 | - | 84 |
| 67-64-1 | 500 | 1210 | 1000 | 2420 | - | 84 |
| 108-65-6 | 50 | 275 | 100 | 550 | - | - |
| 13463-67-7 | - | 10 | - | - | - | - |

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

| CAS | TWA: | STEL: | Ceiling: | Definition: | Criteria: |
|------------|------------------------|------------------------|----------|-------------|-----------|
| 115-10-6 | 400 ppm | 500 ppm | | | |
| | 766 mg/m ³ | 958 mg/m ³ | | | |
| 123-86-4 | 150 ppm | 200 ppm | | | |
| | 724 mg/m ³ | 966 mg/m ³ | | | |
| 67-64-1 | 500 ppm | 1500 ppm | | | |
| | 1210 mg/m ³ | 3620 mg/m ³ | | | |
| 108-65-6 | 50 ppm | 100 ppm | | Sk | |
| | 274 mg/m ³ | 548 mg/m ³ | | | |
| 13463-67-7 | 4 mg/m³ | | | | |

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Version: N°2 (16/06/2022) SOLTA GROUPE

AEROSOL TEINTE RAL 400ML - A400-TEINTE-UFI

Date: 24/05/2023 Page 6/10

Revision: N°1 (01/03/2022)

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of spraying, wear protective clothing against chemical risks and against sprayed liquid (type 4) in accordance with EN14605/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask:

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category:

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A1 (Brown)

Particle filter according to standard EN143:

- P1 (White)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state: Fluid liquid.

Colour

Unspecified

Odour

Odour threshold: Not stated.

Melting point

Melting point/melting range: Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range: Not specified.

Flammability

Flammability (solid, gas): Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%): Not stated. Explosive properties, upper explosivity limit (%): Not stated.

Flash point

Flash point interval: Not relevant.

Auto-ignition temperature

Self-ignition temperature: Not specified.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°2 (16/06/2022) SOLTA GROUPE

AEROSOL TEINTE RAL 400ML - A400-TEINTE-UFI

Date: 24/05/2023 Page 7/10

Revision: N°1 (01/03/2022)

Decomposition temperature

Decomposition point/decomposition range: Not specified.

pН

pH: Not relevant. pH (aqueous solution): Not stated.

Kinematic viscosity

Viscosity: Not stated.

Solubility

Water solubility: Insoluble.
Fat solubility: Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Below 110 kPa (1.10 bar).

Density and/or relative density

Density: <1

Relative vapour density

Vapour density: Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

Aerosols

Chemical combustion heat:

Inflammation time:

Not specified.

Not specified.

Not specified.

Inflammation density:

Inflammation distance:

Flame height:

Not specified.

Not specified.

Not specified.

Not specified.

Not specified.

9.2.2. Other safety characteristics

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- heating
- heat

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

Date: 24/05/2023 Page 8/10

Revision: N°1 (01/03/2022)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 13463-67-7: IARC Group 2B: The agent is possibly carcinogenic to humans.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Version: N°2 (16/06/2022) **SOLTA GROUPE**

AEROSOL TEINTE RAL 400ML - A400-TEINTE-UFI

SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

Date: 24/05/2023 Page 9/10

Revision: N°1 (01/03/2022)

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification:



2.1

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

| ADR/RID | Class | Code | Pack gr. | Label | Ident. | LQ | Provis. | EQ | Cat. | Tunnel |
|---------|-------|------|----------|-------|--------|-----|-------------|----|------|--------|
| | 2 | 5F | - | 2.1 | - | 1 L | 190 327 344 | E0 | 2 | D |
| | | | | | | | 625 | | | |

| IMDG | Class | 2°Label | Pack gr. | LQ | EMS | Provis. | EQ | Stowage Handling | Segregation |
|------|-------|----------|----------|-----------|----------|-------------|----|---------------------|-------------|
| | 2 | See SP63 | - | See SP277 | F-D. S-U | 63 190 277 | E0 | - SW1 SW22 | SG69 |
| | | | | | | 327 344 381 | | | |
| | | | | | | 959 | | | |

| IATA | Class | 2°Label | Pack gr. | Passager | Passager | Cargo | Cargo | note | EQ |
|------|-------|---------|----------|-----------|-----------|-------|--------|--------------|----|
| | 2.1 | - | - | Forbidden | Forbidden | 203 | 150 kg | A1 A145 A167 | E0 |
| | | | | | | | | A802 | |
| | 2.1 | - | - | Forbidden | Forbidden | - | - | A1 A145 A167 | E0 |
| | | | | | | | | A802 | |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

No data available.

- Particular provisions:

No data available.

15.2. Chemical safety assessment

No data available.

Version: N°2 (16/06/2022) SOLTA GROUPE

AEROSOL TEINTE RAL 400ML - A400-TEINTE-UFI

Date: 24/05/2023 Page 10/10

Revision: N°1 (01/03/2022)

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations:

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

UFI : Unique formulation identifier. STEL : Short-term exposure limit TWA : Time Weighted Averages

TMP : French Occupational Illness table TLV : Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02: Flame

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.